


A82.05



WALL SET

[Available with flow control, add **.FC** to end of code - 6 STAR/3.5Lpm WELS RATING]


STANDARD WITH METAL INSERT
OTHER HANDLE OPTIONS



METAL INSERT

**.V2** WITHOUT INSERT**.V3** WHITE CARRARA MARBLE

- Tapware to be installed by a licenced plumber in accordance with AS/NZS 3500:2003
- Recommended working water pressure 150 - 500kPa
- Maximum water temperature is 65 deg C
- After completing the installation check function of tapware and ensure no water leaks.



A82.05

WALL SET

[Available with flow control, add **.FC** to end of code - 6 STAR/3.5Lpm WELS RATING]

Ensure water lines are completely flushed prior to fitting of spindles.

Install the spindles hand-tight until the seal of the spindle firmly makes contact with the seat. Do not over-tighten. Do not tighten seal using the spindle.
Fit washer and screw down locknut over the spindle using an appropriate tube spanner and tighten.


NOTE: Over-tightening the spindles could damage the ceramic discs and in turn, void the manufacturer's warranty.

Seal the wall around the spindle and fit the flange to meet the finished wall surface.

Remove handle insert from spindle, and cut spindle to suit installation.

Re-fit and tighten the handle insert to spindle.

Attach handle to the handle insert and adjust into correct position, and tighten well using an Allen Key.

**NOTE :**

- Seat or Breech Body extensions are NOT recommended in conjunction with this Tapware. Failure to adhere will void warranty.